



Product data sheet

PARAGON 2 ON-GROUND UPLIGHT
PR-50011-M-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Extruded aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39 W	CRI	80
Total flux	3085 lm	LOR	100%
Luminous efficacy	79 lm/W	ULOR	100%
		Total power	39 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 11.65 in
Diameter: 6.30 in
Weight: 2.2 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 39 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C