Product data sheet


CANTO 2000 WHITE 1400LM 3000K RA>80 TRAILING EDGE DIMMING

7021986418668



Design: Svein Knudsen / Andrew Smith Attractive, round luminaire that can be mounted to both walls and ceilings, and both indoors and outdoors. Made of die-cast powder-coated aluminium. Flat diffuser made of UV-stabilised opal polycarbonate. Many variants with both sensors and wireless control, as well as various lumen packages. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 14W 3000K Ra>80 SDCM 3 L70/B50 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block

Light output 1



1 x LED Nominal lamp power Lamp flux Luminous efficacy

CCT

CRI

14 W 1400 lm 100 lm/W 3000 K 80 LOR Total flux Total power

100% 1400 lm 14 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 12.97 in Width: 12.97 in Height: 4.20 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 14 W Appliance Class: I

Protection

IP: 65 IK: 10