Product data sheet

NIKON 4 RECESSED EXTERIOR DOWNLIGHTS NI-80535-VN-W40

LIGMAN










- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K, 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - 6 mm thick front ring is available in stainless steel or aluminium - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Include control gear for NIKON 5, NIKON 6 - Remote driver is included for NIKON 1, NIKON 2, NIKON 3, NIKON 4 - Remote IP box is included for NIKON 1, NIKON 2, NIKON 3, NIKON 4

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	33.3 W	CRI	80
Total flux	3174 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	33.3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.87 in Width: 7.87 in Height: 4.88 in Weight: 2.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 33.3 W Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65 IK: 08

Surface temperature: 40°C