Product data sheet

URBANO TWILIGHT LED 153W 18500LM 4000K IP66 O5 - FOR RESIDENTIAL AREA ROADS REGULATION -15° ... 0° GRAY I 130192.5L08.151.986


LUG



IP 66 IK 08

Professional streetlight luminaire for LED light sources. Luminaire with twilight sensor. Mounting: on pillar ø60/76mm, on outriggers ø60/76mm Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.054 m² Power: 220-240V 50/60Hz Lifetime (L90B10): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, 10kV surge protection, NTC Additional information: Tilt adjustment: 5°, knife switch (for protection class I), access to the driver chamber without the use of tools. The possibility of using one or more power supplies in the luminaire. Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: freeways, express roads, local roads, town roads, residential area roads, area lighting Type of optics: O5 - for residential area roads

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	153 W	CRI	247
Total flux	18500 lm	LOR	100%
Luminous efficacy	121 lm/W	Total power	153 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 28.74 in
Width: 11.61 in
Height: 8.54 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 153 W
Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor

Protection

IP: 66
IK: 08