

Product data sheet


TOTO 2X35/49/80W DALI MEDIUM
3382055
SOLAR



IP
23

ToTo Åpen industriarmatur 2x35/49/80W HF i varmgalvanisert stål MIRO aluminium , 5x2,5mm² gjennomgangskobling


Light output 1



2 x Fluorescent lamp tubular T5

Nominal lamp power	80 W
Lamp flux	6150 lm
Luminous efficacy	70 lm/W
CCT	4000 K
CRI	85


Socket	G5
LOR	95%
Total flux	11692 lm
Total power	167 W



2 x Fluorescent lamp tubular T5

Nominal lamp power	80 W
Lamp flux	6150 lm
Luminous efficacy	70 lm/W
CCT	3000 K
CRI	85


Socket	G5
LOR	95%
Total flux	11692 lm
Total power	167 W



2 x Fluorescent lamp tubular T5


Nominal lamp power	39 W
Lamp flux	3100 lm
Luminous efficacy	74 lm/W
CCT	3000 K
CRI	85

Socket	G5
LOR	95%
Total flux	5893 lm
Total power	80 W




2 x Fluorescent lamp tubular T5

Nominal lamp power	35 W	Socket	G5
Lamp flux	3300 lm	LOR	95%
Luminous efficacy	78 lm/W	Total flux	6274 lm
CCT	4000 K	Total power	80 W
CRI	85		



2 x Fluorescent lamp tubular T5

Nominal lamp power	49 W	Socket	G5
Lamp flux	4300 lm	LOR	95%
Luminous efficacy	78 lm/W	Total flux	8175 lm
CCT	4000 K	Total power	105 W
CRI	85		



2 x Fluorescent lamp tubular T5

Nominal lamp power	49 W	Socket	G5
Lamp flux	4300 lm	LOR	95%
Luminous efficacy	78 lm/W	Total flux	8175 lm
CCT	3000 K	Total power	105 W
CRI	85		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 64.57 in

Width: 6.89 in

Height: 2.95 in

Adjustability

Fixed

Electric

System power: 80-167 W

Protection

IP: 23