Product data sheet

OUTDOOR LIGHTING

V1-S1-00443-40U24-6608050 TORNADO PARKING 80W 5000K NEMA


VARTON



IP 66 IK 09

LED street light luminaire. Tool-free access to the driver. Adjustable spigot. Cast aluminum housing, tempered protective glass. Application: squares and parkings. Installation: pole and side-entry mounted (Ø48mm-60mm). AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Protection class: I Suitable for top end size, mm: 48...60 Mounting method: Side-entry Ingress protection (IP): IP66 Impact resistance: IK09 Power factor: 0,97 Color rendering index: 70-79 Nominal voltage, V: 220...230 https://www.varton.ru/products/ulichnoe-osveshchenie/tornado/tornado-parking-dlya-parkovki/svetodiodnyy-svetilnik-varton-ulichnyy-tornado-parking-kreplenie-na-konsol-80-vt-5000-k-1-10v-nema-r_2/

Light output 1



1 x LED

Nominal lamp power	80 W	LOR	100%
Lamp flux	10800 lm	Total flux	10800 lm
Luminous efficacy	135 lm/W	Total power	80 W
CCT	5000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 24.72 in
Width: 10.47 in
Height: 3.90 in

Adjustability

Fixed

Electric

System power: 80 W

Protection

IP: 66
IK: 09