

Product data sheet


LUCAS PVII (BOLLARD WITH DOOR AND KÜK)
9.881.5497.15
LEIPZIGER LEUCHTEN



IP
55

Decorative luminaire for lanes, driveways, terraces, gardens, and for night illumination and hazardous areas. - Impact-resistant clear/opal polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Unit carrier, crown flange and ornaments made of corrosion-resistant cast aluminium, painted; ground and passivated special steel parts preferably in jet black, RAL 9005 - Housing/upright tube of special steel painted in any RAL or DB colour without surcharge, or special steel, ground and passivated - All electrical components accommodated on a block -Crown detachable for easy maintenance/lamp change - Upright tube with pole door, incl. cable joint box for cable 5x16 mm2 Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

Light output 1



| | | | |
|------------------------------|---------|-------------|--------|
| 1 x Compact fluorescent lamp | | | |
| Nominal lamp power | 26 W | LOR | 40% |
| Lamp flux | 1800 lm | ULOR | 21% |
| Luminous efficacy | 26 lm/W | Total flux | 716 lm |
| CCT | 2899 K | Total power | 28 W |
| CRI | 90 | | |

Mounting mode

Standing / Bollard

Shape and measurements

Height: 37.80 in
Diameter: 6.69 in

Design

Color of housing: Black

Electric

System power: 28 W

Protection

IP: 55