Product data sheet

BASSI WHITE 690LM 3000K RA>80 TWILIGHT

7021986111880


SG ARMATUREN





Design: Hallvard Jakobsen Attractive, square LED wall luminaire that can be installed both indoors and outdoors. Made of die-cast powdercoated aluminium. Diffuser made of UV-stabilised opalescent polycarbonate, two inputs/outputs for cables, option of both visible and hidden cabling, and loopable quick clips. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 11W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Twilight Protection Class II IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1



1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI

11 W 690 lm 63 lm/W 3000 K 80

LOR	100%
ULOR	3%
Total flux	690 lm
Total power	11 W

System power: 11 W Appliance Class: I

Protection

Electric

IP: 65 IK: 10

Adjustability

Mounting mode Wall mounted

Length: 9.45 in Width: 3.07 in

Height: 9.45 in

Shape and measurements

Fixed

Design

Color of housing: White