

Product data sheet


LUMINAIRE ALT BERLIN S 4000K
20.11001.2VXXX
HESS




IP
54

Roof and luminaire cage made of aluminium alloy. Support elements made of cast aluminium. Glass cage closed, luminaires enclosure made of PMMA, clear or structured. With mounting bracket. Pole made of cast silumin aluminium with flange plate.


Light output 1




1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3335 lm	ULOR	100%
Luminous efficacy	119 lm/W	Total flux	3335 lm
CCT	4000 K	Total power	28 W
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3362 lm	ULOR	100%
Luminous efficacy	120 lm/W	Total flux	3362 lm
CCT	4000 K	Total power	28 W
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3268 lm	ULOR	100%
Luminous efficacy	117 lm/W	Total flux	3268 lm
CCT	4000 K	Total power	28 W
CRI	80		


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2435 lm
122 lm/W
4000 K
80

LOR
ULOR
Total flux
Total power

100%
100%
2435 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2454 lm
123 lm/W
4000 K
80

LOR
ULOR
Total flux
Total power

100%
100%
2454 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2386 lm
119 lm/W
4000 K
80

LOR
ULOR
Total flux
Total power

100%
100%
2386 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
1752 lm
63 lm/W
4000 K
80

LOR
ULOR
Total flux
Total power

100%
100%
1752 lm
28 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
1766 lm
63 lm/W
4000 K
80

LOR
ULOR
Total flux
Total power

100%
100%
1766 lm
28 W



1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1716 lm	ULOR	100%
Luminous efficacy	61 lm/W	Total flux	1716 lm
CCT	4000 K	Total power	28 W
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 20.46 in

Width: 17.72 in

Height: 35.44 in

Adjustability

Fixed

Electric

System power: 20-28 W

Protection

IP: 54