



Product data sheet

ATX FELED INDIRECT LINEAR 5K LUMEN NEMA TYPE V 4000 K CCT
 FELEDI5NBUSAD
 APPLETON (EMERSON EGS)



ATX FELED Series Nonmetallic LED Explosionproof Luminaires Ceiling/ Pendant Mount 4000 K CCT/ 80 CRI Pendant/Ceiling Mount BU:-120-277 Vac, 50/60Hz, 170-300 Vdc, BD:-100-240 Vac 50/60 Hz 3/4" NPT Hub Clear polycarbonate cover Zone 1 and 2 Zone 21 & 22 Ex. II 2 GD IP 66 IK 10 Refer to catalog for additional options

Light output 1 (integrated)



Lamp type	LED	CCT	3783 K
Nominal lamp power	49.84 W	CRI	80
Total flux	2612 lm	LOR	100%
Luminous efficacy	52 lm/W	ULOR	4%
		Total power	49.84 W

Mounting mode

Pendant

Shape and measurements

Length: 8.54 in

Width: 46.46 in

Height: 5.71 in

Adjustability

Tiltable, Height adjustable

Electric

System power: 49.84 W

Appliance Class: II

Protection

IP: 67

IK: 10

Explosion zone suitability: 1, 21