
Product data sheet

BARIS 52 LED P GK LACZNIK T 2100LM 840 IP20 I KL. PRM BIALY 17W
936227
LENA LIGHTING



936227 BARIS 52 LED P GK LACZNIK T 2100LM 840 IP20 I KL. PRM BIALY 17W The key feature of L, T, X connectors is that they are equipped with integrated electronics and a diffuser, thanks to which the profile route bends remain illuminated along the entire length. Body is made of anodized aluminium profile in grey or aluminium profile painted white or black (other colors available on request). The optical system is complemented by a dedicated, flexible opal cover that evenly illuminates the connector. There is no division into surface mounted and suspended versions, which make the solution more universal.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	80
Total flux	2100 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	17 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 22.05 in
Width: 22.05 in
Height: 2.72 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Electric

System power: 17 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 03
Designation labels: CE

Other operating numbers

Ambient temperature range: 32...86°F