
Product data sheet

BASIC MAX SURFACE - X1
BX1ASE-830M-D1200
LIGHTNET



LED surface-mounted luminaire for walls or ceilings. Direct light distribution and indirect lighting corona or direct only light distribution. 6 different diameters from 300mm to 1200mm. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. On request: Integration of emergency lighting components, sensor technology.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	266 W	CRI	82
Total flux	26573 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	29%
		Total power	266 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 47.24 in
Diameter: 47.24 in

Adjustability

Fixed

Electric

System power: 266 W

Protection