
Product data sheet


KORNER2
7781-T-5-666-XX
UNILAMP



IP 66 IK 08

KORNER is minimalistic linear shaped pole luminaire and wall light. The use of clear lines, closed surfaces and hidden mounting hardware provide an attractive unobtrusive appearance, and easy installation. The unique 16 stage paint process and use of virtually copper free aluminum alloys guarantee an ultra-long product lifetime. KORNER is suitable for medium mounting heights when using aluminum poles and high mounting heights of up to 8m in combination of steel poles. Existing circular poles can be utilized with the use of the innovative clamping system. KORNER uses high efficacy LED modules and CAD optimized optics. Ready for light management systems using the D4i protocol and Zhaga book 18 interface. Withstanding ambient temperatures of 50°C and electrical surges make KORNER applicable for most challenging environments. KORNER features: Energy saving by offering system efficacy of 120 lm/W Single- or double-sided installation Staggered installation height possible for efficient road and walkway lighting Optional built-in photocell for added energy savings Pre-wired 8000mm long cable

Light output 1



1 x LED

Nominal lamp power	45 W	LOR	9%
Lamp flux	8440 lm	Total flux	729 lm
Luminous efficacy	188 lm/W	Total power	50 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 19.61 in
Width: 5.86 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 50 W
Appliance Class: I

Protection

IP: 66
IK: 08