


Product data sheet

NIX V2 7200 120° E 21 IP65 840 / L-1500 MM (THROUGH WIRE CONNECTION)
19.9902.0004.21
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is polycarbonate. Colour - RAL 9006 (grey). Dimensions: 1480 x 72 x 61 mm. Diffuser: opalescent polycarbonate. Beam angle: (C0-C180) / (C90-C270) - 118° / 106,6°. Light source type: LED. Colour of the light 4000 K. SDCM=6. CRI>80. Lifetime of LED sources: 54000 h L80/B10. Luminaire luminous flux: 7211,4 lm. Power of luminaire: 52,9 W. Luminaire's light efficiency: 136,3 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 33 (B10), 53 (B16), 33 (C10), 53 (C16). Operating temperature range: -20 ÷ 35° C. Protection degree: IP65. Impact resistant: IK10. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED			
Nominal lamp power	52.9 W	LOR	52%
Lamp flux	7211 lm	Total flux	3781 lm
Luminous efficacy	136 lm/W	Total power	52.9 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 58.27 in
Width: 2.83 in
Height: 2.40 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 52.9 W
Appliance Class: I

Protection

IP: 65
IK: 10

Other operating numbers

Ambient temperature range: -4...95°F