


# Product data sheet

PITTSBURGH 1 FLOODLIGHTS, PROJECTORS AND COLUMN PROJECTORS  
PIB-50001-T4B-8030  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Extruded aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Galvanized steel arm mounted - Thermal heat dissipation body - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency polycarbonate lens - Clear toughened glass - Integral control gear - Surge protection 10kV

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 39 W    | CRI         | 80     |
| Total flux         | 3338 lm | LOR         | 100%   |
| Luminous efficacy  | 86 lm/W | ULOR        | 50%    |
|                    |         | Total power | 39 W   |

## Mounting mode

Standing / Bollard, Wall mounted

## Shape and measurements

Length: 8.94 in  
Width: 20.87 in  
Height: 3.54 in  
Weight: 6.5 kg

## Adjustability

Fixed

## Electric

System power: 39 W  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 66  
IK: 08  
Surface temperature: 40°C