Product data sheet


LINEDO_4,5M_AS_11001100
9545AS.842.500.504
RZB



IP 54 IK 03


LINEDO, 137 W, 20000 lm, 840, white, on/off Continuous line luminaire, L 4547 B 58 H 76

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	34.25 W	CRI	80
Total flux	5000 lm	LOR	100%
Luminous efficacy	146 lm/W	Total power	34.25 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	34.25 W	CRI	80
Total flux	5000 lm	LOR	100%
Luminous efficacy	146 lm/W	Total power	34.25 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	34.25 W	CRI	80
Total flux	5000 lm	LOR	100%
Luminous efficacy	146 lm/W	Total power	34.25 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	34.25 W	CRI	80
Total flux	5000 lm	LOR	100%
Luminous efficacy	146 lm/W	Total power	34.25 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 179.02 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 137 W

Protection

IP: 54
IK: 03