


Product data sheet

STYLE II 22011 LED SL CG-S WITH CLEAR COVER
40071356810 + 40071345985
EATON EMERGENCY LIGHTING



• Safety luminaire from high quality, UV-resistant, halogen-free plastic with LED-technology • Modular constructed luminaire series permits combination with various fixing modules • Special LED optical arrangement for efficient illumination of exit routes, suitable for mounting heights up to 6 m, maximum distance from luminaire to luminaire: > 16 m from 3 m mounting height and > 20 m from 4.5 m mounting height • Minimum service requirement due to high service life of the LEDs (up to 50,000 hours) • Simple mounting via quick mounting set (can be pre-assembled) with plug-in connectors for through-wiring • Optionally available IP54 set (for electronic and light source) for increased sealing requirements for indoor rooms or for canopied outdoor areas • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation expenditures by STAR technology • Freely programmable mixed operation of the switching modes per luminaire in one circuit

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	4.4 W	CRI	70
Total flux	107 lm	LOR	100%
Luminous efficacy	24 lm/W	Total power	4.4 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 13.39 in
Width: 7.76 in
Height: 2.36 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 4.4 W
Suitable for feed-through wiring
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Central battery feed-in
Emergency sign: N/A

Protection

IP: 41
IK: 03