Product data sheet

KOMBIC 100 RD 2000 IP43 927 OP DA MA/WH
K11RD2040OP927DMW
LAMP



Round recessed downlight model KOMBIC 100 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring DALI-2 included. Insolation Class II. Lifetime: 100.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED

Nominal lamp power	19.5 W	LOR	100%
Lamp flux	1672 lm	Total flux	1669 lm
Luminous efficacy	86 lm/W	Total power	19.5 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.15 in
Diameter: 3.94 in

Adjustability

Fixed

Electric

System power: 19.5 W
Appliance Class: II

Protection

IP: 43