Product data sheet

LUCAS III (WALL FITTING BEADED) 9.837.3046.16

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure mercury vapour lamp | | | | |
|---------------------------------------|---------|-------------|--|--|
| Nominal lamp power | 50 W | LOR | | |
| Lamp flux | 2000 lm | ULOR | | |
| Luminous efficacy | 28 lm/W | Total flux | | |
| CCT | 3400 K | Total power | | |
| CRI | 54 | | | |



| I x High pressure mercury vapour lamp | | | | |
|---------------------------------------|---------|-------------|---------|--|
| Nominal lamp power | 80 W | LOR | 83% | |
| Lamp flux | 4000 lm | ULOR | 2% | |
| Luminous efficacy | 37 lm/W | Total flux | 3316 lm | |
| CCT | 3400 K | Total power | 89 W | |
| CRI | 54 | | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 59-89 W

Protection

IP: 55

83% 2% 1658 lm 59 W