Product data sheet


6W 3000K 25°
P96L_LARGE
MP LIGHTING



IP 20

Application Interior pendant downlight illumination. Mounting C1 Retrofit to existing standard octagonal box using custom mounting plate (included). C3 Ø4-5/8" x 1/4" (Ø117mm x 6mm) canopy. Mounts to standard octagonal box (not included). C4 4-5/8" Sq. x 1/4" (117mm Sq. x 6mm) canopy. Mounts to standard octagonal box (not included). DC Rotatable and easy to position. Designed for use on 12V or 24V MP dual circuit rail system (sold separately). HD Rotatable and easy to position. Designed for use on 12V or 24V MP horizontal double rail system (sold separately). SR Rotatable and easy to position. Designed for use on 12V or 24V MP single rail system (sold separately). VD Rotatable and easy to position. Designed for use on 12V or 24V MP vertical double rail system (sold separately). Electrical 6 x 1W, 350mA LEDs. 12V AC or 24V DC DC - Powered by remote 24V DC driver. Recommended TLDAV100W24V. Dimmable with 100W 24V driver and controller, 0~10V dimming. Consult factory. AC - Recommended TLW120MT050-01 / TLW277MT050 magnetic transformer (not included). Consult factory for dimming option. Power Consumption 8W Light Output 6.0 Watt, 254lm Warranty 5 years limited warranty Estimated useful life of LED is 50,000 hours. Material Anodized aluminum. RoHS compliant

Light output 1



1 x LED

Nominal lamp power	6 W	LOR	54%
Lamp flux	254 lm	Total flux	136 lm
Luminous efficacy	23 lm/W	Total power	6 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 2.95 in
Width: 2.95 in
Height: 18.00 in

Adjustability

Height adjustable

Electric

System power: 6 W

Protection

IP: 20