


Product data sheet

CERTUS LED 6630LM 4000K RA>80 DALI
5703821162753
SG ARMATUREN



Certus is an IP65 LED luminaire for direct or suspended mounting. Luminaire body made of fibreglass reinforced with polyester, diffuser made of acrylic or resistant polycarbonate, LED diffusers made of polycarbonate and external clips made of stainless steel, equipped with through connection (5x1, 5 mm²) terminating at each end of the luminaire. Light distribution Direct Light source LED 46W 4000K Ra > 80 SDCM 3 L90/B10 > 50.000 hrs Control/Dimming DALI Protection Class I IP65 Energy and approvals CE Materials and finish Housing: Glassfibre, polyester, reinforced Optics: PMMA Polymethylmethacrylat Mounting/Connection Surface, Indoor Max. luminaires per circuit breaker: B10: 13, B16: 20, C10: 21, C16: 34

Light output 1



1 x LED			
Nominal lamp power	46 W	LOR	100%
Lamp flux	6630 lm	ULOR	6%
Luminous efficacy	144 lm/W	Total flux	6630 lm
CCT	4000 K	Total power	46 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.81 in

Width: 6.30 in

Height: 4.17 in

Adjustability

Fixed

Electric

System power: 46 W

Appliance Class: I

Protection

IP: 65

IK: 07