Product data sheet

GRANVIA PRO 15000 WIDE EDD 34 830 / L-1500MM
19.4378.8613.34
LUXIONA



IP 20 IK 06

Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is steel sheet. Colour - RAL 9016 (white). Dimensions: 1500 x 72 x 66 mm. Diffuser: optical system based on PMMA lenses. The efficiency of the optical system is 96,13%. Beam angle: (C0-C180) / (C90-C270) - 86,2° / 84,4°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 13825,1 lm. Power of luminaire: 83,4 W. Luminaire's light efficiency: 165,8 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 13 (B10), 21 (B16), 22 (C10), 32 (C16). Operating temperature range: -20 ÷ 35° C. Protection degree: IP20. Impact resistant: IK06. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



5 x LED

Nominal lamp power	16.68 W	LOR	52%
Lamp flux	2876 lm	Total flux	7540 lm
Luminous efficacy	172 lm/W	Total power	83.4 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 59.06 in
Width: 2.83 in
Height: 2.60 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 83.4 W
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 06

Other operating numbers

Ambient temperature range: -4...95°F