



# Product data sheet

THINDR  
1749.CEN.9  
PSM LIGHTING




built-up ceiling light - fixed - central feeding - with LED driver

## Light output 1 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

## Light output 2 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

## Light output 3 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 4 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 5 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 6 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 7 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 8 (integrated)



Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 9 (integrated)



Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 44.49 in

Width: 1.77 in

Height: 35.83 in

Adjustability

Fixed

Design

Material impression: Aluminum, Brass, Matt

Color of housing: Other colors

Designer: Saskia Mortier

Electric

System power: 34.2 W

Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20

IK: 02