Product data sheet


LOUI BEAMLINE
921655.002.76
RZB



IP 20 IK 03


Series: LESS IS MORE BEAMLINE system Colour: traffic white, matt (RAL 9016) Length: 1682 mm Width: 57 mm Height: 75 mm Suspension length: 2000 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 90 System power: 35 W Rated luminous flux: 2900 lm Beam angle Down: 30° Luminous efficiency: 83 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	11.67 W	CRI	90
Total flux	967 lm	LOR	100%
Luminous efficacy	83 lm/W	ULOR	13%
		Total power	11.67 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11.67 W	CRI	90
Total flux	967 lm	LOR	100%
Luminous efficacy	83 lm/W	ULOR	13%
		Total power	11.67 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11.67 W	CRI	90
Total flux	967 lm	LOR	100%
Luminous efficacy	83 lm/W	ULOR	13%
		Total power	11.67 W

Mounting mode

Pendant

Shape and measurements

Length: 2.24 in

Width: 66.22 in

Height: 2.95 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 35.01 W

Protection

IP: 20

IK: 03