Product data sheet


NUMANCIA XXL 105000 WIDE E IP66 22 740
19.4383.4271.22
LUXIONA



IP 66 IK 09

Outdoor luminaire. Assembly: mounted on poles. The body material is aluminum. Colour - RAL 9007 (dark grey). Dimensions: 887 x 662 x 89 mm. Diffuser: PMMA lenses and hardened transparent glass. The efficiency of the optical system is 83,30%. Beam angle: (C0-C180) / (C90-C270) - 92,8° / 92,6°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>70. Lifetime of LED sources: 108000 h L95/B10. Luminaire luminous flux: 87896 lm. Power of luminaire: 541,6 W. Luminaire's light efficiency: 162,3 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Circuit load capacity: 1 (B10), 1 (B16), 1 (C10), 1 (C16). Operating temperature range: -40 ÷ 50° C. Protection degree: IP66. Impact resistant: IK09. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



3 x LED

Nominal lamp power	180.533 W	LOR	52%
Lamp flux	35162 lm	Total flux	55313 lm
Luminous efficacy	195 lm/W	Total power	541.6 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 34.92 in
Width: 26.06 in
Height: 3.50 in

Adjustability

Tiltable

Design

Color of housing: Anthracite / graphite, Silver gray

Electric

System power: 541.6 W
Appliance Class: I

Protection

IP: 66
IK: 09

Other operating numbers

Ambient temperature range: -40...122°F