

# Product data sheet


LD4B LED 4" ROUND RECESSED DOWNLIGHT  
LD4B10D010 EU4B10209024 4LBWLI1  
COOPER LIGHTING



IP  
47

New construction downlight; open or lensed wall wash, Excellent light control and low aperture brightness, New construction for standard plenum height; ENERGY STAR® qualified, Round die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, W2N Tunable White 2700K-6500K or 2000K-5000K, Lumens: 1,000-6,000; 0-10V dimming down to 1%, WaveLinx and DLVP connected lighting systems compatibility, Plaster lathing ring accessory offered for flush reflector transition

## Light output 1 (integrated)



Lamp type	LED	CCT	2400 K
Nominal lamp power	9.9 W	CRI	90
Total flux	768 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	9.9 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 3.94 in  
Diameter: 4.50 in

## Adjustability

Fixed

## Electric

System power: 9.9 W

## Protection

IP: 47