Product data sheet


LINEAR LIGHTING
V1-R0-00304-05A00-2001640 T-LINE 1,0 M 16W 4000K EM 1H
VARTON



IP 40 IK 01

• Stand-alone luminaire made of extruded aluminum • Diffuser and covers are included in package Application • Retail spacess • Administrative facilities Installation • Surface-mounted • Suspended (optional) Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Surface mounting/hangable Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact resistance: IK01 Power factor: 0,9 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/t-line/t-line-1-0-m/cvetilnik-varton-t-line-1-m-16-vt-odinochnyy-podvesnoy-nakladnoy-1006kh70kh90-mm-4000-k-ral9003-bely_2/

Light output 1



1 x LED

Nominal lamp power	16 W	LOR	100%
Lamp flux	1500 lm	Total flux	1500 lm
Luminous efficacy	94 lm/W	Total power	16 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 39.61 in
Width: 2.76 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 16 W

Protection

IP: 40
IK: 01