



Product data sheet

RECESSED CEILING LUMINAIRE GEO 3 OFFICE 1 LAMP 30W 3800LM C
2005.8047 - GEO3 CR1496X115 LED3800-830 WH DALI
REGENT



Recessed ceiling luminaire Geo 3 Office 1 lamp, with LED, system power: 30 W, standby power 0.5 W, luminous flux of luminaire 3800 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, housing in steel sheet white powder coated, specular louvre in aluminium brilliant polished, 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0315), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20 / IP40, glow wire test 850 °C, impact strength: IK 07 this product contains a light source of energy efficiency class D and EPREL registration number: 992206 L = 1496 mm, B = 115 mm, EL = 1486 mm, EB = 100 mm, ET = 100 mm

Light output 1



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3800 lm	Total flux	3801 lm
Luminous efficacy	136 lm/W	Total power	30 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 60.87 in

Width: 4.53 in

Height: 2.91 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 30 W

Appliance Class: I

Protection

IP: 40

IK: 07