Product data sheet


STICK
7268-L-3-669-XX
UNILAMP



IP 66 IK 10

STICK is a family of cylindrical-shaped light column and wall luminaire giving symmetrical light distribution on illuminated surfaces. The recommended mounting height is between 3 – 4 meters above ground. It is operated with high power LED. STICK is assembled with anti-glare suppression louvers that direct the light downward onto the illuminated surface. Clear PMMA cover protects the lamp compartment from the ingress of dust and water. It is generally installed in walkways, gardens, parks, commercial areas and open spaces to provide the general lighting from mid-high level. Anchor unit for concrete foundation are is available. spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • PMMA protective cover. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium louvers. • GFR PA6.6 Terminal block. • Weather proof grommet. • Pole light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED

Nominal lamp power	23 W	LOR	88%
Lamp flux	4440 lm	Total flux	3899 lm
Luminous efficacy	193 lm/W	Total power	26 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Length: 7.36 in
Width: 7.36 in
Height: 136.77 in

Adjustability

Fixed

Electric

System power: 26 W
Appliance Class: I

Protection

IP: 66
IK: 10