
Product data sheet

RECESSED DIRECTIONAL SPOTLIGHT NOVO 2 ROUND INNER RING SET BACK ROUND 8.9W 1000LM CRI > 90 4000K 47M..
2010.9567 - NOVO2 RS SB CR80 LED1000-940-L35 WH DALI


REGENT



IP 44 IK 07

Recessed directional spotlight Novo 2 Round inner ring set back, with LED, system power: 8.9 W, standby power 0.5 W, luminous flux of luminaire 1000 lm, colour rendering index CRI > 90, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, rated current: 47 mA, direct light emission, housing in die-cast aluminium, with ceiling trim, white, RAL 9016, with lens, 35, 1 integral control gear, DALI2, high-quality die-cast aluminium housing, reduced installation time thanks to fully pre-assembled luminaire, including connection to control gear, with through-wiring option, suitable for ceiling thicknesses from 1 to 45 mm protection class II, ingress protection IP20 / IP44, glow wire test 850 °C, impact strength: IK 07 this product contains a light source of energy efficiency class D and EPREL registration number: 2018957 Ø = 96 mm, ceiling cutout ø 80 mm up to 90 mm, ET = 98 mm, swivelling 15°

Light output 1



1 x LED

Nominal lamp power	9.2 W	LOR	100%
Lamp flux	1000 lm	Total flux	1000 lm
Luminous efficacy	109 lm/W	Total power	8.9 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 0.04 in
Width: 0.04 in
Height: 0.04 in
Weight: 0.761 kg

Adjustability

Rotatable, Tiltable

Design

Color of housing: White

Electric

System power: 8.9 W
Appliance Class: II

Protection

IP: 44
IK: 07