Product data sheet


TILLA II DA LED (OPTIC 058)
9.503.8328.07058-3
LEIPZIGER LEUCHTEN



IP 65

recom. pole height: 4.00m – 7.00m light standards: low and medium lighting requirements lamp: incl. 1, 2 or 3 DA+ LED modules, easy to replace colour temperature: 4.000K neutral white or 3.000K warm white (other colour temperatures on request) surge protection: 10kV LED gear: incl. driver, up to 100,000 hours; with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for emergency LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90 /B10 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction, dimming, DALI or CLEVER LIGHT optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: street optics, square optics, area optics, cycle path optics (other optics on request) luminaire head: incl. cap and base made of aluminium; powder coated colour: DB 703; other RAL or DB colour without extra cost on request glazing: PMMA RESIST, clear, high-impact resistant wiring: completely wired; via a plug and socket connector below the luminaire head installation: for post top ø 60mm or ø 76mm accessory: cable, column, pole accessories, backlight shield – to be ordered separately application areas: residential and local distributor roads, car parks, schools, hotels, factory premises, paths, squares, parks

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	76 W	CRI	70
Total flux	10820 lm	LOR	20%
Luminous efficacy	142 lm/W	ULOR	20%
		Total power	76 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 22.83 in
Diameter: 11.81 in
Weight: 10 kg

Adjustability

Height adjustable

Design

Color of housing: Other colors

Electric

System power: 76 W

Protection

IP: 65