



Product data sheet

SRT-SYSTEM IP20-SRGVCDA XP/2250 LED - GERÄTETRÄGER VARIABEL CENTRAL.LINE.OPTIC | DEVICE MOUNT VARIABLE..
15000 840 DALI2 VW RAL 9016 (SRT+19565026870)
REGIOLUX



SRT-Quick-fit mounting system, Variable device mount, Modullänge/2250. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Variable position on the mounting rail. Housing colour traffic white RAL 9016. Performance level: Xtreme Performance (XP) - For the most demanding tasks, the best possible performance, durability and warranty period at the highest level, Light distribution direct double asymmetrical distribution by means of Central.Line.Optic of PMMA plastic, the lens optics ensure ease of installation and are easy to maintain thanks to the easy-to-clean surface. The density of the single-row lens arrangement ensures that the points merge to form a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 5-pin, quick-fit plug connector in the light run with free phase pre-selection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 2299mm x 55mm x 37mm Beam angle: 80°(C0)/100° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG0 LED service life: 100000h L90/B10 (Tq 40°C), 100000h L90/B50 (Tq 45°C) Nominal luminous flux: 14988lm Luminaire luminous efficiency: 203lm/W Control gear: Electronic driver DALI2 (1 pcs.) System output: 74W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 45°C) Ambient temperatur: ta -20°C to 45°C Special properties: Ready for IoT UGR lat./long.: max. 24.1 / 24.1 Certification mark: IP20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 10 years (ta -20°C to 40°C, suspended mounting > 30cm)
7 years (ta -20°C to 45°C) Regiolux GmbH Type: SRGVCDAXP /2250 LED 15000 840 DALI2 vw RAL 9016 Article number: 19565026870 Product deep link: <https://www.regiolux.de/en/article/19565026870> General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	73.7 W	CRI	80
Total flux	14988 lm	LOR	100%
Luminous efficacy	203 lm/W	Total power	73.7 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 90.63 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 73.7 W
Appliance Class: 0

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC

Design

Color of housing: White