Product data sheet


GIMBAL RECESSED SPOTLIGHT CARDA COMPETENCE 28W CRI > 80 300
2003.1637 - CARDAC CA CR180X180 LED3000-830 15 WH ONF
REGENT



IP 20

Gimbal recessed spotlight Carda Competence with LED, system power: 28 W, luminous flux of luminaire 3000 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 2, lifetime LED L90 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, in die-cast aluminium, with ceiling trim, white, similar to RAL 9016, super narrow, (N), 15°, operating unit included in delivery, ON/OFF, protection class II, ingress protection IP20, glow wire test 850 °C, this product contains a light source of energy efficiency class D and EPREL registration number: 864034 L = 192 mm, B = 192 mm, A = 42 mm, EL = 180 mm, EB = 180 mm, ET = 146 mm, swivelling 40°

Light output 1



1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	3000 lm	Total flux	3014 lm
Luminous efficacy	111 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.56 in
Width: 7.56 in
Height: 5.75 in
Weight: 1.2 kg

Adjustability

Cardanic

Design

Color of housing: White

Electric

System power: 28 W
Appliance Class: II

Protection

IP: 20