


# Product data sheet

GAVLE 1 RECESSED CEILING LUMINAIRES  
GAV-80061-O-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Diffuser for light output control O - Opal diffuser UGR <19 Trendy ring-shaped surface, recessed and pendant mounted ceiling luminaires with symmetrical up and down lighting for general or specialized lighting requirements. Lighting control system. · Wireless control employing the Bluetooth® 4.0 protocol controlled via Ligman's mobile App or physical control via xPress switch · Daylight and occupancy sensor options Extruded aluminium bended profile with 316 grade stainless steel fasteners. Opal PMMA diffuser for glare control. Built-in driver. Passive thermal management. Surface ceiling mountings with the use of steel support and screws. Pendant mounting with the application of adjustable steel suspension (1m) complete with electrical wires in white. Applications: private residences, offices schools and universities, retail, showrooms, galleries, museums, conference halls, meeting rooms, banks, bars, restaurants, hotel and similar installations.

## Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

## Light output 2 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 3 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 4 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 5 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 6 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 7 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 8 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 9 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 10 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 11 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Light output 12 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	17.2 W	CRI	80
Total flux	1755 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	17.2 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.54 in  
Diameter: 157.48 in  
Weight: 35.6 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 206.4 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor, Presence sensor

Protection

IP: 20  
Surface temperature: 40°C  
Designation labels: CE, ENEC, UL