Product data sheet

ECLDISPLAYCASVW_BLACK ECLDISPLAYCASVW_2800K_PROFILE 2040DEG_MAX ZOOM






1 v I FD





EclDisplay is a range of revolutionary and flexible LED spotlights designed for galleries, retail and any public venue where an advanced but classical looking fixture is needed, with several control options, sources and optic versions available to precisely meet any application. The EclDisplay CAS VW is the version of the EclDisplay range made with integrated CASAMBI control on-board, leaving to System Integrators to install this luminaire in venues with their own wiring distribution and control. EclDisplay CAS VW includes a high-efficiency 35W Warm White + Cold White (Variable White - VW) LED capable of delivering a full tuneable White from 2700K to 5600K, and it is completed with a wide selection of optional profile (zoom and static) or wash lenses, and other optical accessories like louvres and snoots, making it a truly a multipurpose fixture. Main features: CASAMBI control on-board 35W Variable White LED capable to deliver a full Tunable White from 2700K to 5600K Multiple lens options: profile (zoom and static) or wash optics

Light output 1



I X LLD	
Nominal lamp power	31.7 W
Lamp flux	886 lm
Luminous efficacy	28 lm/W
CCT	2871 K
CRI	97

Electric

System power: 31.7 W Controller: DMX, DALI Color adjustable Appliance Class: I

LOR

Total flux

Total power

Protection

IP: 20 IK: 08

Surface temperature: 65°C Designation labels: CE

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 39.37 in Width: 39.37 in Height: 39.37 in

Adjustability

Rotatable, Tiltable, Free

100%

888 lm

31.7 W