


Product data sheet

CUBIC EVOLUTION SUSPENDED - R4
CR4LEE-830M-L640-YB
LIGHTNET



LED pendant luminaire. Direct-indirect light distribution. Luminaire body with minimalistic overall height made of aluminium profile. Surface natural anodised or white, graphite, black or champagne coated as well as polished aluminium. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Direct part using precision lenses with louvre for wide rotationally symmetrical light distribution with high glare limitation (UGR<16). Louvre available in various colour combinations. Indirect light with innovative lens technology for wide-angle ceiling illumination. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim). Colour temperature 2700K, 3000K, 3500K or 4000K. Binning initial $\leq$ Mac Adam 3. Colour rendering CRI>80 or CRI>90. Height adjustable Y-cord suspension or parallel-cord suspension with transparent power supply cable, colour of ceiling rose matching luminaire body. On request: Soft-touch black or red sheathed supply line.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27 W	CRI	82
Total flux	3104 lm	LOR	100%
Luminous efficacy	115 lm/W	ULOR	73%
		Total power	27 W

Mounting mode

Pendant

Electric

System power: 27 W

Shape and measurements

Length: 25.20 in
Width: 7.87 in
Height: 0.98 in

Protection

Adjustability

Height adjustable