


Product data sheet

HARRIER 1 IN-GROUND LUMINAIRES
HA-60385-N-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 135,000, 300,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - 6 mm thick front ring in stainless steel or aluminium - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - High-efficiency PMMA lens - Durable silicone rubber gasket - Clear, 10 mm thick, toughened glass - Integral control gear - Remote driver is included for HA-60385, HA-60386, HA-60395, HA-60396 - Recessing box in high-density polyethylene is included - Suitable for walk-over with a maximum load of 200 kg

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	8 W	CRI	80
Total flux	423 lm	LOR	100%
Luminous efficacy	53 lm/W	ULOR	100%
		Total power	8 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 5.91 in
Diameter: 4.72 in
Weight: 0.7 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 8 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 67
IK: 10
Surface temperature: 40°C