Product data sheet


CIRCULAR INWARD 3 RINGS (Ø3000 Ø2000 Ø1200)
CD4G-00V9AZOUEF
LEDSC4



IP 20

LedsC4 Circular Inward 3 Rings (ø3000 ø2000 ø1200) CD4G-00V9AZOUEFV1 Pendant for indoor use. For uplighting and downlighting. Structure finish: Gold. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 3030 Product height (mm): 7000 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 371.4W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 19558. Real lm/W: 51. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 381. Power factor: 0.90. Dimmable equipment included: ON-OFF.


Light output 1



1 x LED

Nominal lamp power	185.5 W	LOR	100%
Lamp flux	9391 lm	ULOR	50%
Luminous efficacy	51 lm/W	Total flux	9391 lm
CCT	2700 K	Total power	185.5 W
CRI	90		


Light output 2



1 x LED

Nominal lamp power	126.4 W	LOR	100%
Lamp flux	6459 lm	ULOR	50%
Luminous efficacy	51 lm/W	Total flux	6459 lm
CCT	2700 K	Total power	126.4 W
CRI	90		

Light output 3



1 x LED

Nominal lamp power	69.1 W	LOR	100%
Lamp flux	3708 lm	ULOR	50%
Luminous efficacy	54 lm/W	Total flux	3708 lm
CCT	2700 K	Total power	69.1 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 118.11 in
Width: 118.11 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 381 W
Appliance Class: I

Protection

IP: 20