## Product data sheet

LUCAS VI (WALL FITTING) 9.832.3066.15 LEIPZIGER LEUCHTEN






CRI

High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp					
Nominal lamp power	125 W	LOR			
Lamp flux	6800 lm	Total flux			
Luminous efficacy	42 lm/W	Total power			
CCT	3400 K				

54

LOR	84%
Total flux	5697 lm
Total power	137 W

$\square$	"ATT
$\times$	+XX
XX	X
Xt	+ + + + +

1 x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR	84%	
Lamp flux	4000 lm	Total flux	3351 lm	
Luminous efficacy	38 lm/W	Total power	89 W	
CCT	3400 K			
CRI	54			

Mounting mode	Electric
Wall mounted	System power: 89-137 W
Shape and measurements	Protection
Height: 22.44 in	IP: 55

## 9

P

H Diameter: 22.44 in