Product data sheet

NADJA II (WALL FITTING) 9.845.3046.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp		
Nominal lamp power	50 W	
Lamp flux	2000 lm	
Luminous efficacy	26 lm/W	
CCT	3400 K	
CRI	54	

LOR	77%
Total flux	1543 lm
Total power	59 W



1 x High pressure mercury vapour lamp		
Nominal lamp power	80 W	
Lamp flux	4000 lm	
Luminous efficacy	35 lm/W	
CCT	3400 K	
CRI	54	

LOR	77%
Total flux	3087 lm
Total power	89 W
rotal porrel	05 11

Mounting mode

Wall mounted

Shape and measurements

Height: 20.08 in Diameter: 20.08 in Electric

System power: 59-89 W

Protection

IP: 55