Product data sheet

EVA II 9.898.3162.05

LEIPZIGER LEUCHTEN









For high light requirements, mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized - Large aluminium reflector for max. light output, inside in special white paint - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Unit carrier made of hot die cast aluminium, corrosion-resistent, outside painted in colour - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury	vapour lamp
Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	29 lm/W
CCT	3400 K
CRI	54

LOR	59%
ULOR	14%
Total flux	4016 lm
Total power	137 W



1 x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR	59%	
Lamp flux	4000 lm	ULOR	14%	
Luminous efficacy	27 lm/W	Total flux	2362 lm	
CCT	3400 K	Total power	89 W	
CRI	54			

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in Diameter: 15.75 in Electric

System power: 89-137 W

Protection

IP: 55