


Product data sheet

INDIGO LED VTB 4000K DALI CLO
24651-456
FAGERHULT



Installation Recessed mounting in suspended ceilings. Unventilated or ventilated ceilings. Two optional designs: VTB – for suspended ceilings with visible T-bars (25 or 15 mm). HB – for suspended ceilings with concealed T-bars and symmetrical ceiling tiles. Four suspension fittings included. For fixed roofs (plaster etc.) suspension fittings for an HB body can be ordered separately. Do not cover with insulation. For detailed information, see the installation instructions. Connection Connected to 2.5 mm² 3-way terminal block with the possibility of through-wiring. With additional number for 5-way terminal block dimming. Can also be supplied with mains cable and earthed plug or chassis mounted snap-in connector. Designed by Luminaire body of white enamelled (RAL 9016) sheet steel. Louvre Diffuser in Opal acrylic. Miscellaneous The luminaire has a switch for high/ low flow easily accessible at the rear of the luminaire. Always delivered set at high flow.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	34 W	CRI	80
Total flux	3400 lm	LOR	100%
Luminous efficacy	100 lm/W	Total power	34 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.46 in
Width: 23.46 in
Height: 5.98 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 34 W

Protection

IP: 20