


Product data sheet

FLOODLIGHTS
V1-I0-70590-04L07-6512040 FL-PRO 100/120 W 120W 4000K 60°
VARTON




IP
66

IK
08

Professional floodlight with a high quality lighting. Wide range of optics and CCT. Material: Cast aluminum body, acrylic optic, protective tempered glass. Installation: Surface-mounted using an adjustable bracket. Angle of rotation: 0° to 180°. The luminaire has a wire for connecting to the mains. Wire length 0.3 meters. Application: Floodlighting. Architectural. Outdoor areas. Industrial facilities. Warehouses. Input voltage (AC, 50Hz), V: 100...305 AC frequency, Hz: 50 Input voltage (DC), V: 145...430 Flicker, %: 5 Climatic modification and category of placement: YXL11 Height/depth, mm: 90 Length, mm: 447 Protection class: I Fire danger class: П-I,II,IIa,III Ingress protection (IP): IP66 Impact resistance: IK08 Width, mm: 309 Power factor: 0,95 <https://www.varton.ru/products/prozhektory/fl-pro/fl-pro-100-120-vt/svetodiodnyy-svetilnik-var-ton-prozhektor-fl-pro-60-120-vt-4000-k-ral7045-muar/>

Light output 1



1 x LED			
Nominal lamp power	120 W	LOR	100%
Lamp flux	16700 lm	Total flux	16700 lm
Luminous efficacy	139 lm/W	Total power	120 W
CCT	4000 K		
CRI	70		

Mounting mode

Ceiling mounted

Electric

System power: 120 W

Shape and measurements

Length: 17.60 in

Width: 12.17 in

Height: 3.54 in

Protection

IP: 66

IK: 08

Adjustability

Fixed