




# Product data sheet

861 COMFORTLIGHT UGR<LT/>19 4000K CRI 80 37W CLD WHITE  
150459-00  
DISANO



Housing: galvanised steel. Optics: dark light longitudinal and transversal double parabolic louvers, made of high-gloss, plated 99.85 aluminium, anti-dazzle and anti-iridescent, very low luminance, 65°. : UGR<lt/>19, according to standard EN 12464. Coating: pre-painted in oven with polyester resin, UV-stabilised, phosphate pre-treatment. Wiring: quick, no need to open the fixture. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: - inspection door and terminal block for electricity connection. - Protective film. Mounting: recessed only surface mounting on max. 38mm T-beams.

## Light output 1



1 x LED			
Nominal lamp power	37 W	LOR	100%
Lamp flux	3990 lm	Total flux	3990 lm
Luminous efficacy	108 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.31 in  
Width: 23.46 in  
Height: 3.54 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 37 W  
Appliance Class: I

## Protection

IP: 20  
IK: 07  
Designation labels: CE