


Product data sheet

FLUM060-S 228S-260I-135GE/840, B
228S-260I-135GE/840
HALLA




228S-260I-135GE/840, B Luminaire surface/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Rounded Size: 711 x 60 x 65 mm Type of installation: Surface, Suspended Distribution: Direct Optics type: Microprisma Protection class: I Voltage: 220-240V

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	80
Total flux	178 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	2%
		Total power	2.48 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	80
Total flux	178 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	2%
		Total power	2.48 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	80
Total flux	178 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	2%
		Total power	2.48 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	80
Total flux	178 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	2%
		Total power	2.48 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.48 W	CRI	80
Total flux	178 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	2%
		Total power	2.48 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 5.51 in

Width: 2.36 in

Height: 2.56 in

Adjustability

Fixed

Electric

System power: 12.4 W

Appliance Class: I

Protection

IP: 20

IK: 01