Product data sheet

CEILING LUMINARIE TALON M1, 4770LM 29W 830/3000K, LAMP COVER PMMA CLEAR, WIDE BEAM, CDP-PRISM SCREEN 6851428319-H1


NORKA



IP 65 IK 08

Leuchte für Deckenanbau und Deckeneinbau aus Aluminium mit LED-Array-Bestückung, 1- oder 2-lampig. Einsetzbar in U- und S-Bahnhöfen, Fußgängerunterführungen, Personentunnel, Passerellen, Schwimmbädern (siehe Optionen), Verkehrsflächen, unter Überdachungen und Fassaden. Silberfarbig eloxiertes Aluminium-Profilgehäuse. Abklappbare Abschlussscheibe. Einsetzbar im Innen- und Außenbereich gemäß Schutzart IP 65. Schutzklasse II. Glasklare Abschlussscheibe aus PMMA oder PC (bruchsicher) mit Druckbild oder Abschlussscheibe weiß bedruckt aus PMMA oder PC (bruchsicher) bzw. PMMA Transopal® (schlagzäh) ohne Druckbild. Innenliegender Aluminium-Reflektor, extrem breitstrahlend. Ausführung mit integrierter Prismenscheibe zur rotationssymmetrischen Entblendung (CDP), breitstrahlend. Eingebautes Betriebsgerät, Versorgungsspannung 230 V AC/DC. Anschlussfertig über eine rückseitige Kabelmembran. 2 kV Transientenfilter. Einzelmontage. Optional Lichtbandausführung oder am NORKA Medienkanal 285. Deckenbefestigung über rückwärtige 2-/4-Punkt-Befestigung. Weight: 5,0 kg; Fire resistance D: YES; Ball impact resistant: NO; Light sensor: NO; Version: m1; Lamp service life: L80 B10 > 60,000 h at +40°C; Extreme-temperature: -35°C to +40°C; Housing material: aluminium; Colour housing: Aluminium; Material / Cover: PMMA clear; Cover: lamp cover; Light distribution: wide beam; ENEC / VDE: NO / NO; Lamp power: 26 W; max. System power: 29 W; Colour temperature: White, 830/3000 K, Ra > 80; Protection class: II; IP-rating: IP65; Type of gear: LED operating device current-controlled, No dim function, 230 V - 240 V AC/DC; Through-wiring: without; Usage: architectural lighting, railway platforms/stations, facade illumination, storage/cellar/technical side rooms, swimming pool/chlorine resistant (optional), sports/multipurpose hall, petrol station, underpasses; Impact strength: IK08;

Light output 1



1 x LED

Nominal lamp power	29 W	LOR	96%
Lamp flux	4770 lm	Total flux	4561 lm
Luminous efficacy	164 lm/W	Total power	29 W
CCT	3000 K		
CRI	83		

Mounting mode

Ceiling mounted, Ceiling recessed, Contact rail

Shape and measurements

Length: 11.22 in
Width: 11.22 in
Height: 2.87 in

Adjustability

Fixed

Electric

System power: 29 W
Appliance Class: II

Protection

IP: 65
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -31...104°F

Design

Material impression: Aluminum

Color of housing: Silver gray