


Product data sheet

MICROSPY IN TRIMLESS OK 92730
24112 9220
DELTA LIGHT




Luminaire, ceiling recessed (indoor use) from Deltalight, named MICROSPY IN TRIMLESS OK 92730, available in the colour(s): black, white. For recessed mounting, a round opening (for installing a custom mounting kit) is needed and a min. depth for recessing of 75 mm. This luminaire is equipped with LED array 3,9-5,1W / CRI>90 (R9: 56) / 2700K / 385-480lm with an optional driver, suitable for currents of 350mA to 450mA. Light distributor: lens 30°.


Light output 1




1 x LED			
Nominal lamp power	5 W	LOR	73%
Lamp flux	480 lm	Total flux	349 lm
Luminous efficacy	96 lm/W	Total power	5 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	4 W	LOR	73%
Lamp flux	385 lm	Total flux	280 lm
Luminous efficacy	96 lm/W	Total power	5 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	5 W	LOR	73%
Lamp flux	480 lm	Total flux	349 lm
Luminous efficacy	96 lm/W	Total power	5 W
CCT	2700 K		
CRI	90		


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

4 W
385 lm
96 lm/W
2700 K
90

LOR
Total flux
Total power

73%
280 lm
5 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

5 W
480 lm
96 lm/W
2700 K
90

LOR
Total flux
Total power

73%
349 lm
5 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

4 W
385 lm
96 lm/W
2700 K
90

LOR
Total flux
Total power

73%
280 lm
5 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

5 W
480 lm
96 lm/W
2700 K
90

LOR
Total flux
Total power

73%
349 lm
5 W

**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

4 W
385 lm
96 lm/W
2700 K
90

LOR
Total flux
Total power

73%
280 lm
5 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.04 in

Diameter: 1.02 in

Weight: 0.1 kg

Electric

System power: 5 W

Appliance Class: II

Protection

IP: 20

Designation labels: CE