


Product data sheet

INDUSTRIAL AND WAREHOUSE LIGHTING
V1-I0-70638-04D55-6525050 OLYMP 2.0 GL 250 W 250W 5000K DALI 15X50°
VARTON



Medium-power Industrial luminaire with wide range of wattage and optics. Housing: heatsink made of extruded aluminum, assembly and mounting elements made of steel. Secondary optics - PMMA/PC. Tempered glass. Installation: Surface-mounted using an adjustable bracket. Angle of rotation: 0° to 180°, step of 7,5°. The luminaire has a wire for connecting to the mains. Wire length 0.3 meters. Application: Outdoor areas. Industrial facilities. Warehouses and fire hazardous zones classified as P-IIa according to Electrical Installations Regulations. Input voltage (AC, 50Hz): 100...305 AC frequency: 50 Input voltage (DC): 130...300 Flicker: 5 Climatic modification and category of placement: УХЛ2 Protection class: I Ingress protection (IP): IP65 Impact resistance: IK08 Power factor: 0,95 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/olymp-gl-2-0/olymp-gl-2-0-250-vt/svetodiodnyy-svetilnik-var-ton-promyshlenny-olymp-gl-2-0-250-vt-5000k-klass-zashchity-ip65-15-kh50-r_1/

Light output 1



1 x LED			
Nominal lamp power	250 W	LOR	100%
Lamp flux	35720 lm	Total flux	35722 lm
Luminous efficacy	143 lm/W	Total power	250 W
CCT	5000 K		
CRI	70		

Mounting mode

Ceiling mounted

Electric

System power: 250 W

Shape and measurements

Length: 21.06 in

Width: 10.94 in

Height: 6.69 in

Protection

IP: 65

IK: 08

Adjustability

Fixed