

Product data sheet

HB 501
221175.002.2
RZB




IP
40


IK
06

Series: HB 501 Flat decorative round LED surface-mounted luminaire. Housing: plastic (polycarbonate). Diffuser: plastic (polycarbonate), opal. Base and diffuser are sealed together. MultiColour: Colour temperature adjustable via switching element for 3000K (factory setting), 4000K and 5700K. Quick mounting adapter steel sheet, white powder-coated, with bayonet fastening. Driver integrated. Colour: white Diameter: 300mm Height: 48mm Lamp: LED Socket: without socket Colour temperature: 3000K, 4000K, 5700K Colour rendering index (CRI): 80 System power: 17W Rated luminous flux: 1750lm Luminous efficiency: 103lm/W System power 2: 17W Rated luminous flux 2: 1750lm Luminous efficiency 2: 103lm/W System power 3: 17W Rated luminous flux 3: 1750lm Luminous efficiency 3: 103lm/W Control gear: EB Protection class: I Type of protection: IP40


Light output 1



1 x LED			
Nominal lamp power	17 W	LOR	100%
Lamp flux	1750 lm	Total flux	1750 lm
Luminous efficacy	103 lm/W	Total power	17 W
CCT	5700 K		
CRI	80		



1 x LED			
Nominal lamp power	17 W	LOR	100%
Lamp flux	1750 lm	Total flux	1750 lm
Luminous efficacy	103 lm/W	Total power	17 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	17 W	LOR	100%
Lamp flux	1750 lm	Total flux	1750 lm
Luminous efficacy	103 lm/W	Total power	17 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 1.89 in

Diameter: 11.81 in

Adjustability

Fixed

Electric

System power: 17 W

Protection

IP: 40

IK: 06