


# Product data sheet

NEW TORCIA LED  
528008  
FLOS




Outdoor cylindrical bollard light. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Opal polycarbonate diffuser for LED versions

## Light output 1



<b>1 x LED</b>			
Nominal lamp power	8.7 W	LOR	100%
Lamp flux	756 lm	ULOR	55%
Luminous efficacy	84 lm/W	Total flux	757 lm
CCT	6000 K	Total power	9 W
CRI	70		



<b>1 x Compact fluorescent lamp</b>			
Nominal lamp power	26 W	Socket	G24D_3
Lamp flux	1800 lm	LOR	100%
Luminous efficacy	200 lm/W	ULOR	55%
CCT	3000 K	Total flux	1801 lm
CRI	82	Total power	9 W

## Mounting mode

Pole top mounted, Standing / Bollard

## Shape and measurements

Height: 9.06 in  
Diameter: 3.15 in

## Adjustability

Fixed

## Electric

System power: 9 W  
Appliance Class: I

## Protection

IP: 65  
IK: 09